

View Online at <https://aerobasegroup.com/nsn/5320-01-361-9127>

Fastener Length:

0.410 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.172 inches and 0.176 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.208 inches and 0.218 inches

Expansion Device:

Serrated stem-type w

Grip Length:

0.042 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Nickel alloy 400 locking ring or nickel alloy r-405 locking ringaluminum alloy 5056 mandrelnickel alloy 600 stem

Material Specification:

Qq-n-281 federal specification all material responses locking ringqq-a-430 federal specification single material response mandrelams 5665
assn standard single material response stem

Surface Treatment:

Anodize mandrel and chromate mandrel

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response mandrel and mil-c-5541 military specification 2nd treatment response mandrel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.