

View Online at <https://aerobasegroup.com/nsn/5320-01-361-9127>

**Fastener Length:**

0.410 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.172 inches and 0.176 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.208 inches and 0.218 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

0.042 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Nickel alloy 400 locking ring or nickel alloy r-405 locking ringaluminum alloy 5056 mandrelnickel alloy 600 stem

**Material Specification:**

Qq-n-281 federal specification all material responses locking ringqq-a-430 federal specification single material response mandrelams 5665  
assn standard single material response stem

**Surface Treatment:**

Anodize mandrel and chromate mandrel

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response mandrel and mil-c-5541 military specification 2nd treatment response mandrel

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.