NSN 5320-01-361-9127

Blind Rivet - Page 1 of 1

A040a0

Mil-a-8625 spec.

Mil-std (military Standard):



View Online at https://aerobasegroup.com/nsn/5320-01-361-9127 **Fastener Length:** 0.410 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) Shank Diameter: Between 0.172 inches and 0.176 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** Between 0.208 inches and 0.218 inches **Expansion Device:** Serrated stem-type w **Grip Length:** 0.042 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Nickel alloy 400 locking ring or nickel alloy r-405 locking ringaluminum alloy 5056 mandrelnickel alloy 600 stem **Material Specification:** Qq-n-281 federal specification all material responses locking ringqq-a-430 federal specification single material response mandrelams 5665 assn standard single material response stem **Surface Treatment:** Anodize mandrel and chromate mandrel **Surface Treatment Specification:** Mil-a-8625 military specification 1st treatment response mandrel and mil-c-5541 military specification 2nd treatment response mandrel Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: