NSN 5320-01-362-4784

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-362-4784

g					
Thread Class:					
3a					
Thread Direction:					
Right-hand					
Fastener Length:					
Between 2.135 inches and 2.155 inches					
Head Style:					
Err-090					
Head Height:					
Between 0.077 inches and 0.090 inches					
Shank Diameter:					
Between 0.2797 inches and 0.2807 inches					
Shank Style:					
Err-090					
Head Major Diameter:					
Between 0.435 inches and 0.460 inches					
Lubrication:					
Cetyl alcohol, specification 305, hi-shear corp					
Grip Length:					
Between 1.745 inches and 1.755 inches					
Thready Qty Per Inch (tpi):					
28					
Min. Tensile Strength (psi):					
160000 pounds per square inch					
Thread Size:					
0.250 inches					
Shear Strength:					
11800 double pounds per square inch					
Material:					
Steel					
Material Specification:					
Mil-s-5000 military specification single material response					
Surface Treatment:					
Cadmium					
Surface Treatment Specification:					
Qq-p-416, tyii, cl2 federal specification single treatment response					
Thread Series Designator:					
Unjf					
Specification Data:					
73197-hl220-8-28 professional/industrial association specification					

Shelf Life: N/a

NSN 5320-01-362-4784

Pin-rivet - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.