

View Online at <https://aerobasegroup.com/nsn/5320-01-362-6203>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.5650 inches and 0.5850 inches

Head Style:

Err-090

Head Height:

Between 0.0640 inches and 0.0740 inches

Width Between Flats:

Between 0.1040 inches and 0.1190 inches

Shank Diameter:

Between 0.2016 inches and 0.2026 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.3570 inches and 0.3770 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.2450 inches and 0.2550 inches

Thread Qty Per Inch (tpi):

32

Thread Size:

0.1900 inches

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.