

View Online at <https://aerobasegroup.com/nsn/5320-01-362-7272>

Fastener Length:

0.412 inches

Head Style:

Universal

Head Height:

Between 0.054 inches and 0.064 inches

Shank Diameter:

Between 0.125 inches and 0.129 inches

Head Major Diameter:

Between 0.238 inches and 0.262 inches

Expansion Device:

Plain stem-type t

Grip Length:

Between 0.251 inches and 0.312 inches

Special Features:

Sleeve color plain

Material:

Iron alloy 660 locking ring or steel comp 304 locking ringaluminum alloy 5056 sleevesteel comp 8740 stem

Material Specification:

Ams 5731 assn standard 1st material response locking ring or ams 5639 assn standard 2nd material response locking ringq-q-a-430 federal specification single material response sleeveams 6322 assn standard single material response stem

Surface Treatment:

Passivate locking ringchromate sleeve cadmium stem and chromate stem

Surface Treatment Specification:

Q-q-p-35 federal specification single treatment response locking ringmil-c-5541 military specification single treatment response sleeveq-q-p-416 type ii, class 2 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.