NSN 5320-01-362-7921

Pin-rivet - Page 1 of 1



21

View Online at https://aerobasegroup.com/nsn/5320-01-362-792
Fastener Length:
Between 0.741 inches and 0.761 inches
Head Style:
Err-090
Head Height:
Between 0.128 inches and 0.147 inches
Shank Diameter:
Between 0.2480 inches and 0.2495 inches
Shank Style:
Pin-rivet, multiple grooved
Head Major Diameter:
Between 0.390 inches and 0.430 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 0.532 inches and 0.594 inches
Features Provided:
Casehardened and sealant vent groove
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
77.0 rockwell superficial 15-n and 82.0 rockwell superficial 15-n
Shear Strength:
95000 single pounds per square inch
Material:
Steel comp 8740 or steel comp 4340 or steel comp 4140
Material Specification:
Astm a547 assn standard all material responses
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Specification Data:
80205-nas1468 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A528u0