# NSN 5320-01-363-6136

Pin-rivet - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5320-01-363-6136



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.685 inches and 0.705 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

## Shank Diameter:

Between 0.2095 inches and 0.2100 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

#### **End Application:**

W/s: aircraft, hawkeye e-2c; fms-aircraft, hawkeye e-2c: aircraft, tomcat f-14

#### Grip Length:

Between 0.250 inches and 0.260 inches

## Thready Qty Per Inch (tpi):

32

## Thread Size:

0.190 inches

#### **Countersink Angle:**

100.0 degrees

#### Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## Surface Treatment:

Anodize

#### **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

## Unit Of Measure:

---

#### **Demilitarization:**

No

Fiig:

A528u0