

View Online at <https://aerobasegroup.com/nsn/5320-01-363-7298>

Fastener Length:

0.678 inches

Head Style:

Tapered pan

Head Height:

Between 0.125 inches and 0.135 inches

Shank Diameter:

Between 0.197 inches and 0.199 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.305 inches and 0.332 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.469 inches and 0.532 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Locking collar green

Material:

Iron alloy 660 locking ring or steel comp 316 locking ringiron alloy 660 sleeveiron alloy 660 stem

Material Specification:

Ams 5737 assn standard 1st material response locking ring or ams 5690 assn standard 2nd material response locking ringams 5737 assn standard single material response sleeveams 5737 assn standard single material response stem

Surface Treatment:

Passivate locking ringpassivate sleeve or cadmium sleeve and chromate sleevepassivate stem

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response locking ringqq-p-35 federal specification 1st treatment response sleeve or qq-p-416, type 2, cl 2 federal specification 2nd treatment response sleeveqq-p-35 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-f-8975 spec.