

View Online at <https://aerobasegroup.com/nsn/5320-01-363-7305>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.685 inches and 0.705 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.0791 inches and 0.0806 inches

**Shank Diameter:**

Between 0.2250 inches and 0.2255 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.3253 inches and 0.3303 inches

**End Application:**

W/s: aircraft, hawkeye e-2c; fms-aircraft, hawkeye e-2c; aircraft, tomcat f-14

**Grip Length:**

Between 0.250 inches and 0.260 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Countersink Angle:**

100.0 degrees

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:**

Anodize

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0