NSN 5320-01-363-7313

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-363-7313 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.980 inches and 1.000 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2540 inches and 0.2545 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.5018 inches and 0.5066 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corporation and dry film **Grip Length:** Between 0.3750 inches and 0.3850 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-363-7313

Pin-rivet - Page 2 of 2



Fiig:

A528u0