
## NSN 5320-01-363-8488

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.370 inches and 1.390 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

## Shank Diameter:

Between 0.3170 inches and 0.3175 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.6287 inches and 0.6335 inches

#### Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corporation and dry film

## Grip Length:

Between 0.625 inches and 0.635 inches

## Thready Qty Per Inch (tpi):

24

## Thread Size:

0.312 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

## Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Anodize

#### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

# NSN 5320-01-363-8488

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

