## NSN 5320-01-364-3650

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-364-3650



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.536 inches and 0.576 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.061 inches and 0.069 inches

## Width Between Flats:

Between 0.0947 inches and 0.0967 inches

## Shank Diameter:

Between 0.2641 inches and 0.2651 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.398 inches and 0.413 inches

## Grip Length:

Between 0.126 inches and 0.188 inches

## Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

## Shear Strength:

108000 single pounds per square inch

## Material:

Steel comp 8740 or steel comp 4340

## **Material Specification:**

Aisi assn standard all material responses

## Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response

## **Thread Series Designator:**

Unjf

## Specification Data:

80205-nas4450 professional/industrial association standard

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-364-3650

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

