## NSN 5320-01-364-4827

Solid Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-364-4827

Between 0.428 inches and 0.448 inches

**Head Style:** 

Undersized oval countersunk

**Head Height:** 

Between 0.003 inches and 0.005 inches

**Shank Diameter:** 

Between 0.155 inches and 0.158 inches

**Shank Style:** 

Straight w/radius chamfered tip

**Head Major Diameter:** 

Between 0.2396 inches and 0.2469 inches

**Head Minor Diameter:** 

0.185 mils and 0.195 centimeters

**Countersink Height:** 

0.0372 inches

**Shear Strength:** 

41000 single pounds per square inch

**Countersink Angle:** 

Between 99.5 degrees and 100.5 degrees

**Special Features:** 

Color clear

**Heat Treatment:** 

T-73 solution heat treated

Material:

Aluminum alloy 7050

**Material Specification:** 

Qq-a-430 federal specification single material response

**Surface Treatment:** 

Anodize

**Surface Treatment Specification:** 

Mil-a-8625, type 2, cl 1 military specification single treatment response

**Specification Data:** 

80205-nas1097 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A040a0

## NSN 5320-01-364-4827

Solid Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.