# NSN 5320-01-364-5103

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-364-5103



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.188 inches and 1.208 inches

#### Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.3765 inches and 0.3813 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

### Grip Length:

Between 0.558 inches and 0.568 inches

## Thready Qty Per Inch (tpi):

32

### Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.190 inches

#### Shear Strength:

95000 single pounds per square inch

### **Countersink Angle:**

100.0 degrees

### **Special Features:**

Grit blast top of head, with color blue on thread end

# Material:

Titanium alloy uns r56400

# Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

--

# NSN 5320-01-364-5103

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

