

View Online at <https://aerobasegroup.com/nsn/5320-01-364-9237>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.740 inches and 0.760 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0801 inches

Shank Diameter:

Between 0.1625 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.326 inches and 0.330 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.433 inches and 0.443 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

210000 pounds per square inch

Thread Size:

0.164 inches

Shear Strength:

125000 single pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Grit blast top of head, color green on thread end

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

H1-shear specification 258, cagec 73197 mfr ref single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0