NSN 5320-01-364-9240

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Head Style:

Thread Direction:

Fastener Length:

Between 1.573 inches and 1.593 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-364-9240

Flush countersunk
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2485 inches and 0.2495 inches
Shank Style:
Head Major Diameter:
Between 0.502 inches and 0.507 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 1.183 inches and 1.193 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
210000 pounds per square inch
Thread Size:
0.250 inches
Shear Strength:
125000 single pounds per square inch
125000 single pounds per square inch Countersink Angle:
Countersink Angle:
Countersink Angle: 100.0 degrees
Countersink Angle: 100.0 degrees Special Features:
Countersink Angle: 100.0 degrees Special Features: Grit blast top of head, color green on thread end
Countersink Angle: 100.0 degrees Special Features: Grit blast top of head, color green on thread end Material:
Countersink Angle: 100.0 degrees Special Features: Grit blast top of head, color green on thread end Material: Nickel alloy 718
Countersink Angle: 100.0 degrees Special Features: Grit blast top of head, color green on thread end Material: Nickel alloy 718 Material Specification:
Countersink Angle: 100.0 degrees Special Features: Grit blast top of head, color green on thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response
Countersink Angle: 100.0 degrees Special Features: Grit blast top of head, color green on thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment:
Countersink Angle: 100.0 degrees Special Features: Grit blast top of head, color green on thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate
Countersink Angle: 100.0 degrees Special Features: Grit blast top of head, color green on thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Countersink Angle: 100.0 degrees Special Features: Grit blast top of head, color green on thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: H1-shear specification 258, cagec 73197 mfr ref single treatment response
Countersink Angle: 100.0 degrees Special Features: Grit blast top of head, color green on thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: H1-shear specification 258, cagec 73197 mfr ref single treatment response Thread Series Designator:
Countersink Angle: 100.0 degrees Special Features: Grit blast top of head, color green on thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: H1-shear specification 258, cagec 73197 mfr ref single treatment response Thread Series Designator:

NSN 5320-01-364-9240

Pin-rivet - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0