## NSN 5320-01-364-9243

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-364-9243 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.302 inches and 1.322 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0801 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3256 inches and 0.3304 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.995 inches and 1.005 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.164 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Grit blast top of head, with color blue on thread end Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-364-9243

Pin-rivet - Page 2 of 2



| _  |    | •• | • • |     |     |   |    |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш  | 112 | rız | 211 | n | ٠. |
|    |    |    |     |     |     |   |    |

No

Fiig:

A528u0