## NSN 5320-01-364-9248

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-364-9248 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.815 inches and 0.835 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3570 inches and 0.3770 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** W/s: aircraft, b-2 bomber (atb) **Grip Length:** Between 0.495 inches and 0.505 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches **Special Features:** Hi-kote aluminum coating, with color light blue on thread end Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-364-9248

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0