NSN 5320-01-364-9268

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-364-9268 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.440 inches and 0.460 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style: Head Major Diameter:** Between 0.3570 inches and 0.3770 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.120 inches and 0.130 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Grit blast top of head, with color blue on thread end Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-364-9268

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0