## NSN 5320-01-364-9270

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-364-9270



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.847 inches and 1.867 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.130 inches and 0.140 inches

#### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3740 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.5650 inches and 0.6000 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 1.307 inches and 1.317 inches

## Thready Qty Per Inch (tpi):

24

#### Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.375 inches

## Shear Strength:

95000 single pounds per square inch

#### **Special Features:**

Grit blast top of head, with color blue on thread end

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-364-9270

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

