NSN 5320-01-364-9280

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-364-9280 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.927 inches and 0.947 inches **Head Style:** Err-090 **Head Height:** Between 0.055 inches and 0.065 inches Width Between Flats: Between 0.0791 inches and 0.0801 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3060 inches and 0.3220 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.620 inches and 0.630 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.164 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Grit blast top of head, with color blue on thread end Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-364-9280

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0