

View Online at <https://aerobasegroup.com/nsn/5320-01-364-9283>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.135 inches and 1.155 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.502 inches and 0.507 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.745 inches and 0.755 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

210000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

125000 single pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Grit blast top of head, color green on thread end

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

H1-shear specification 258, cagc 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0