

View Online at <https://aerobasegroup.com/nsn/5320-01-365-0500>

Fastener Length:

Between 0.194 inches and 0.254 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.125 inches and 0.129 inches

Head Major Diameter:

Between 0.206 inches and 0.224 inches

Expansion Device:

Plain stem-type t

Grip Length:

0.063 inches

Countersink Angle:

Between 99.0 degrees and 100.0 degrees

Material:

Iron alloy 660 locking ring or steel comp 304 locking ringaluminum alloy 5056 sleeve steel comp 8740 stem

Material Specification:

Ams 5731 assn standard 1st material response locking ring or ams 5639 assn standard 2nd material response locking ring q-q-a-430 federal specification single material response sleeve ams 6322 assn standard single material response stem

Surface Treatment:

Passivate locking ring chromate sleeve cadmium stem and chromate stem

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response locking ring mil-c-5541 military specification single treatment response sleeve qq-p-416, ty ii, cl 2 federal specification single treatment response stem

Specification Data:

80205-nas9302 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-c-5541 spec.