

View Online at <https://aerobasegroup.com/nsn/5320-01-365-0503>

Fastener Length:

0.750 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.171 inches and 0.176 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.281 inches and 0.290 inches

Expansion Device:

Plain stem-type t

Grip Length:

Between 0.501 inches and 0.562 inches

Countersink Angle:

Between 98.5 degrees and 101.5 degrees

Material:

Nickel alloy 400 locking ring or nickel alloy r-405 locking ringaluminum alloy 5056 sleeve nickel alloy 600 stem

Material Specification:

Qq-n-281 federal specification all material responses locking ringqq-a-430 federal specification single material response sleeveams 5665 assn standard single material response stem

Surface Treatment:

Anodize sleeve or chromate sleeve

Surface Treatment Specification:

Mil-a-8625 federal specification 1st treatment response sleeve or mil-c-5541 federal specification 2nd treatment response sleeve

Specification Data:

80205-nas1939 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.