

View Online at <https://aerobasegroup.com/nsn/5320-01-365-0503>

**Fastener Length:**

0.750 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.171 inches and 0.176 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.281 inches and 0.290 inches

**Expansion Device:**

Plain stem-type t

**Grip Length:**

Between 0.501 inches and 0.562 inches

**Countersink Angle:**

Between 98.5 degrees and 101.5 degrees

**Material:**

Nickel alloy 400 locking ring or nickel alloy r-405 locking ringaluminum alloy 5056 sleevenickel alloy 600 stem

**Material Specification:**

Qq-n-281 federal specification all material responses locking ringqq-a-430 federal specification single material response sleeveams 5665  
assn standard single material response stem

**Surface Treatment:**

Anodize sleeve or chromate sleeve

**Surface Treatment Specification:**

Mil-a-8625 federal specification 1st treatment response sleeve or mil-c-5541 federal specification 2nd treatment response sleeve

**Specification Data:**

80205-nas1939 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.