

View Online at <https://aerobasegroup.com/nsn/5320-01-365-0504>

Fastener Length:

0.782 inches

Head Style:

Universal

Head Height:

Between 0.080 inches and 0.090 inches

Shank Diameter:

Between 0.200 inches and 0.204 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.356 inches and 0.394 inches

Expansion Device:

Plain stem-type t

Grip Length:

Between 0.501 inches and 0.562 inches

Material:

Nickel alloy 400 locking ring or nickel alloy r-405 locking ringaluminum alloy 5056 sleevenickel alloy 600 stem

Material Specification:

Qq-n-281 federal specification all material responses locking ringqq-a-430 federal specification single material response sleeveams 5665
assn standard single material response stem

Surface Treatment:

Anodize sleeve or chromate sleeve

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response sleeve or mil-c-5541 military specification 2nd treatment response sleeve

Specification Data:

80205-nas1938 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.