

View Online at <https://aerobasegroup.com/nsn/5320-01-365-0505>

Fastener Length:

0.592 inches

Head Style:

Tapered pan

Head Height:

Between 0.062 inches and 0.070 inches

Shank Diameter:

Between 0.162 inches and 0.164 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.250 inches and 0.272 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.406 inches and 0.470 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Locking collar green

Material:

Iron alloy 660 locking ring or steel comp 316 locking ringiron alloy 660 sleeveiron alloy 660 stem

Material Specification:

Ams5737 assn standard 1st material response locking ring or ams5690 assn standard 2nd material response locking ringams5737 assn standard single material response sleeveams5737 assn standard single material response stem

Surface Treatment:

Passivate locking ringpassivate sleeve or cadmium sleeve and chromate sleevepassivate stem

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response locking ringqq-p-35 federal specification 1st treatment response sleeve or qq-p-416 type 2, cl 2 federal specification 2nd treatment response sleeveqq-p-35 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-f-8975 spec.