

View Online at <https://aerobasegroup.com/nsn/5320-01-365-0505>

**Fastener Length:**

0.592 inches

**Head Style:**

Tapered pan

**Head Height:**

Between 0.062 inches and 0.070 inches

**Shank Diameter:**

Between 0.162 inches and 0.164 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.250 inches and 0.272 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.406 inches and 0.470 inches

**Shear Strength:**

95000 single pounds per square inch

**Special Features:**

Locking collar green

**Material:**

Iron alloy 660 locking ring or steel comp 316 locking ringiron alloy 660 sleeveiron alloy 660 stem

**Material Specification:**

Ams5737 assn standard 1st material response locking ring or ams5690 assn standard 2nd material response locking ringams5737 assn standard single material response sleeveams5737 assn standard single material response stem

**Surface Treatment:**

Passivate locking ringpassivate sleeve or cadmium sleeve and chromate sleevepassivate stem

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response locking ringqq-p-35 federal specification 1st treatment response sleeve or qq-p-416 type 2, cl 2 federal specification 2nd treatment response sleeveqq-p-35 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-f-8975 spec.