

View Online at <https://aerobasegroup.com/nsn/5320-01-365-0508>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.582 inches and 0.607 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

0.2001 inches

**Head Major Diameter:**

0.317 inches

**Tip Diameter:**

0.1964 inches

**Lubrication:**

Dry film and cetyl alcohol

**Grip Length:**

Between 0.302 inches and 0.317 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

125000 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp xm-13

**Material Specification:**

Ams-5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1724 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0