## NSN 5320-01-365-0524

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-365-0524 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.723 inches and 1.743 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Style: Head Major Diameter:** Between 0.7550 inches and 0.7604 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.183 inches and 1.193 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Grit blast top of head, with color blue on thread end Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-365-0524

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0