

View Online at <https://aerobasegroup.com/nsn/5320-01-365-1259>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.7520 inches and 0.7720 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.2016 inches and 0.2026 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.4320 inches and 0.4420 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.1900 inches

Countersink Angle:

100.0 degrees

Material:

Steel comp 431

Material Specification:

Ams 5628 assn standard single material response or mil-s-18732 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.