

View Online at <https://aerobasegroup.com/nsn/5320-01-365-1794>

Fastener Length:

0.448 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.093 inches and 0.097 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.169 inches and 0.189 inches

Expansion Device:

Serrated stem-type w

Lubrication:

Dry film

Grip Length:

Between 0.251 inches and 0.312 inches

Countersink Angle:

Between 98.5 degrees and 101.5 degrees

Material:

Nickel alloy r-405 locking ring or nickel alloy 400 locking ring iron alloy 660 sleeve iron alloy 660 stem

Material Specification:

Qq-n-281 federal specification single material response locking ring assn 5737 standard single material response sleeve assn 5737 standard single material response stem

Surface Treatment:

Passivate sleeve and cadmium sleeve and chromate sleeve passivate stem

Surface Treatment Specification:

Qq-p-35 assn standard 1st treatment response sleeve and qq-p-416 type 2, cl 2 assn standard 2nd treatment response sleeve qq-p-35 assn standard single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0