

View Online at <https://aerobasegroup.com/nsn/5320-01-365-2171>

Thread Class:

3a

Thread Direction:

Left-hand

Fastener Length:

Between 1.065 inches and 1.085 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.104 inches and 0.119 inches

Shank Diameter:

Between 0.1886 inches and 0.1896 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.297 inches and 0.302 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.745 inches and 0.755 inches

Thread Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

lil-kote aluminum coating per iii-shear specification 294 and cetyl alcohol lubeper iii-shear specification 305

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment Specification:

Per hi shear specification 294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0