

View Online at <https://aerobasegroup.com/nsn/5320-01-365-2171>

**Thread Class:**

3a

**Thread Direction:**

Left-hand

**Fastener Length:**

Between 1.065 inches and 1.085 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.104 inches and 0.119 inches

**Shank Diameter:**

Between 0.1886 inches and 0.1896 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.297 inches and 0.302 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 0.745 inches and 0.755 inches

**Thread Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Shear Strength:**

95000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

lil-kote aluminum coating per iii-shear specification 294 and cetyl alcohol lubeper iii-shear specification 305

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

**Surface Treatment Specification:**

Per hi shear specification 294 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0