

View Online at <https://aerobasegroup.com/nsn/5320-01-365-4939>

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.2175 inches and 0.2195 inches

**Head Major Diameter:**

0.386 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.219 inches and 0.282 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Double oversize

**Material:**

Iron alloy 660 locking ring or steel comp 316 locking ringsteel comp 4027 sleeve or steel comp 4037 sleevesteel comp 8740 stem

**Material Specification:**

Ams 5737 assn standard 1st material response locking ring or ams 5690 assn standard 2nd material response locking ringaisi 4027 assn standard 1st material response sleeve or aisi 4037 assn standard 2nd material response sleeve mil-s-6049 military specification single material response stem

**Surface Treatment:**

Cadmium locking ring and passivate locking ringcadmium sleevecadmium stem

**Surface Treatment Specification:**

Qq-p-416 federal specification 1st treatment response locking ring and qq-p-35 federal specification 2nd treatment response locking ringqq-p-416 federal specification single treatment response sleeveqq-p-416 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6049 spec.