

View Online at <https://aerobasegroup.com/nsn/5320-01-365-4943>

**Fastener Length:**

0.385 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.093 inches and 0.097 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.169 inches and 0.189 inches

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Dry film

**Grip Length:**

Between 0.188 inches and 0.250 inches

**Countersink Angle:**

Between 98.5 degrees and 101.5 degrees

**Material:**

Nickel alloy r-405 locking ring or nickel alloy 400 locking ringiron alloy 660 sleeveiron alloy 660 stem

**Material Specification:**

Qq-n-281 cl b monel federal specification 1st material response locking ring or qq-n-281 cl a monel federal specification 2nd material response locking ringams 5737 assn standard single material response sleeveams 5737 assn standard single material response stem

**Surface Treatment:**

Passivate sleeve and cadmium sleeve and chromate sleevepassivate stem

**Surface Treatment Specification:**

Qq-p-35 federal specification 1st treatment response sleeve and qq-p-416 ty2 cl 2 federal specification 2nd treatment response sleeveqq-p-35 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0