

View Online at <https://aerobasegroup.com/nsn/5320-01-365-5939>

Thread Class:

3a

Thread Direction:

Right-hand

Identification Code Color:

Orange

Fastener Length:

Between 0.7600 inches and 0.7800 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.5026 inches and 0.5111 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.3700 inches and 0.3800 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

210000 pounds per square inch

Thread Size:

0.2500 inches

Shear Strength:

125000 single pounds per square inch

Countersink Angle:

130.0 degrees

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Hi-shear spec. 258 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0