NSN 5320-01-365-7276

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Orange

Thread Direction:

Fastener Length:

Head Style:

Head Height:

Hole Diameter:

Shoulder Diameter:

Shoulder Length:

Shank Diameter: 0.1900 inches Shank Style:

Head Major Diameter:


Hole Depth:

Lubrication: Solid film Grip Length:

Thread Size: 0.190 inches Shear Strength:

Identification Code Color:

3a



Between 1.060 inches and 1.080 inches Countersunk w/reverse chamfer Between 0.045 inches and 0.055 inches Between 0.104 inches and 0.119 inches Between 0.2095 inches and 0.2100 inches Between 0.625 inches and 0.635 inches Between 0.295 inches and 0.315 inches Between 0.115 inches and 0.135 inches Between 0.625 inches and 0.635 inches 115000 single pounds per square inch

Countersink Angle:

45.0 degrees

Special Features:

32 thds per in.

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response



NSN 5320-01-365-7276

Pin-rivet - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

