

View Online at <https://aerobasegroup.com/nsn/5320-01-366-1227>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.2490 inches and 0.2530 inches

Shank Style:

Self-plugging high clinch shank

Head Major Diameter:

Between 0.4760 inches and 0.4800 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.2510 inches and 0.3750 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Aluminum alloy 5056 sleeve steel comp 1006 stem or steel comp 1008 stem or steel comp 1010 stem or steel comp 1012 stem or steel comp 1015 stem or steel comp 1016 stem or steel comp 1018 stem or steel comp 1019 stem or steel comp 1021 stem or steel comp 1022 stem or steel comp 1026 stem or steel comp 1030 stem or steel comp 1035 stem or steel comp 1038 stem or steel comp 1524 stem or steel comp 1541 stem

Material Specification:

Mil-w-7986 military specification single material response sleeve stem a-545 assn standard single material response stem

Surface Treatment:

Anodize sleeve or chromate sleeve

Surface Treatment Specification:

Mil-a-8625, type 2, cl 1 military specification single treatment response sleeve or mil-c-5541, cl 1a military specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-w-7986 spec.