## NSN 5320-01-366-1238

Pin-rivet - Page 1 of 2

3a

28

View Online at https://aerobasegroup.com/nsn/5320-01-366-1238

**Thread Class: Thread Direction: Right-hand** Identification Code Color: Green **Fastener Length:** Between 1.1975 inches and 1.2175 inches **Head Style:** Err-090 **Head Height:** Between 0.0800 inches and 0.0900 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches Shank Diameter: Between 0.2485 inches and 0.2495 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.4150 inches and 0.4400 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** Wsd: aircraft, b-2 bomber (atb) Grip Length: Between 0.8075 inches and 0.8175 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 210000 pounds per square inch **Thread Size:** 0.2500 inches Shear Strength: 125000 single pounds per square inch **Criticality Code Justification:** Feat **Special Features:** Weapon system essential Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response



## NSN 5320-01-366-1238

Pin-rivet - Page 2 of 2



Surface Treatment:

Passivate

Surface Treatment Specification:

Hi-shear spec. 258, cagec 73197 mfr ref single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0