## NSN 5320-01-366-1242

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-366-1242

view Online at https://derobasegroup.com/hsr//3520-01-300-1242
Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Blue
Fastener Length:
Between 1.1350 inches and 1.1550 inches
Head Style:
Err-090
Head Height:
Between 0.0800 inches and 0.0900 inches
Width Between Flats:
Between 0.0947 inches and 0.9670 inches
Shank Diameter:
Between 0.2485 inches and 0.2495 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.4150 inches and 0.4400 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.7450 inches and 0.7550 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.2500 inches
Shear Strength:
95000 single pounds per square inch
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Hi-shear spec. 294, cagec 73197 mfr ref single treatment response
Thread Series Designator:

Unjf

## NSN 5320-01-366-1242

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0