NSN 5320-01-366-1261

Pin-rivet - Page 1 of 2

Thread Class:

3a





Thread Direction: Right-hand Identification Code Color: Orange **Fastener Length:** Between 2.935 inches and 2.955 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.045 inches and 0.055 inches Hole Diameter: Between 0.104 inches and 0.119 inches **Shoulder Diameter:** Between 0.2250 inches and 0.2255 inches Shoulder Length: Between 2.500 inches and 2.510 inches Shank Diameter: 0.190 inches Shank Style: Err-090 Head Major Diameter: Between 0.295 inches and 0.315 inches Hole Depth: Between 0.115 inches and 0.135 inches Lubrication: Solid film Grip Length: Between 2.500 inches and 2.510 inches **Thread Size:** 0.190 inches Shear Strength: 115000 single pounds per square inch **Countersink Angle:** 45.0 degrees **Special Features:** 32 thds per in . Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response

NSN 5320-01-366-1261

Pin-rivet - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

