NSN 5320-01-366-1272

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-366-1272
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.065 inches and 1.085 inches
Head Style:
Err-090
Head Height:
Between 0.064 inches and 0.074 inches
Width Between Flats:
Between 0.0791 inches and 0.0806 inches
Shank Diameter:
Between 0.1885 inches and 0.1895 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.357 inches and 0.377 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
End Application:
W/s: aircraft, b-2 bomber (atb)
Grip Length:
Between 0.745 inches and 0.755 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.190 inches
Shear Strength:
95000 single pounds per square inch
Special Features:
Color light blue on thread end
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Surface Treatment:
Aluminum alloy
Surface Treatment Specification:

ourrace rreatment opecanous.

Hi-shear specification 294, cagec 73197 mfr ref single treatment response

NSN 5320-01-366-1272Pin-rivet - Page 2 of 2



inread Series Designato
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A528u0