NSN 5320-01-366-1281

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-366-1281

View Offiline at https://derobasegroup.com/nsn/3320-01-300-1201
Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Blue
Fastener Length:
Between 0.4400 inches and 0.4600 inches
Head Style:
Err-090
Head Height:
Between 0.0791 inches and 0.0806 inches
Width Between Flats:
Between 0.0791 inches and 0.0806 inches
Shank Diameter:
Between 0.1885 inches and 0.1895 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.3570 inches and 0.3770 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.1200 inches and 0.1300 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.1900 inches
Shear Strength:
95000 single pounds per square inch
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Hi-shear spec. 294, cagec 73197 mfr ref single treatment response
Thread Series Designator:

Unjf

NSN 5320-01-366-1281

Pin-rivet - Page 2 of 2



_				
c	hο	JIF.		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0