## NSN 5320-01-366-2867

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-366-2867
Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Blue
Fastener Length:
Between 1.0625 inches and 1.0825 inches
Head Style:
Err-090
Head Height:
Between 0.0930 inches and 0.1060 inches
Width Between Flats:
Between 0.1895 inches and 0.1930 inches
Shank Diameter:
Between 0.4360 inches and 0.4370 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.6410 inches and 0.6760 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.4325 inches and 0.4425 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Thread Size:
0.4375 inches
Shear Strength:
125000 single pounds per square inch
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Hi-shear spec. 294, cagec 73197 mfr ref single treatment response
Thread Series Designator:

Unjf

## NSN 5320-01-366-2867

Pin-rivet - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0