

View Online at <https://aerobasegroup.com/nsn/5320-01-366-3614>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.615 inches and 1.635 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.102 inches and 0.112 inches

**Width Between Flats:**

Between 0.1270 inches and 0.1295 inches

**Shank Diameter:**

Between 0.3115 inches and 0.3120 inches

**Shank Style:**

**Head Major Diameter:**

Between 0.475 inches and 0.505 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 1.120 inches and 1.130 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

210000 pounds per square inch

**Thread Size:**

0.312 inches

**Shear Strength:**

125000 single pounds per square inch

**Special Features:**

Grit blast top of head with color green on thread end

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Hi-shear specification 258, cagec 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0