NSN 5320-01-366-3614

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Head Style: Err-090

Head Height:

Thread Direction:

Fastener Length:

Between 1.615 inches and 1.635 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-366-3614

Between 0.102 inches and 0.112 inches
Width Between Flats:
Between 0.1270 inches and 0.1295 inches
Shank Diameter:
Between 0.3115 inches and 0.3120 inches
Shank Style:
Head Major Diameter:
Between 0.475 inches and 0.505 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 1.120 inches and 1.130 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
210000 pounds per square inch
Thread Size:
0.312 inches
Shear Strength:
125000 single pounds per square inch
Special Features:
Grit blast top of head with color green on thread end
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Hi-shear specification 258, cagec 73197 mfr ref single treatment response
Thread Series Designator:
Unjf

NSN 5320-01-366-3614

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0