# NSN 5320-01-366-4235

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-366-4235

# Thread Direction:

**Right-hand** 

# Fastener Length:

Between 10.86 millimeters and 11.36 millimeters

# Head Style:

Err-090

# **Head Height:**

Between 0.95 millimeters and 1.20 millimeters

# Width Between Flats:

Between 1.61 millimeters and 1.64 millimeters

# Shank Diameter:

Between 3.978 millimeters and 3.990 millimeters

# Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

Between 6.25 millimeters and 6.65 millimeters

# Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# Grip Length:

Between 3.87 millimeters and 4.13 millimeters

# Thread Size:

4.0 millimeters

# **Thread Pitch In Millimeters:**

0.70

# Thread Tolerance Class:

4h external

# Material:

Titanium alloy

# Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

# Thread Series Designator:

lso m

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A528u0