

View Online at <https://aerobasegroup.com/nsn/5320-01-366-4582>

**Fastener Length:**

1.3190 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.2641 inches and 0.2651 inches

**Head Major Diameter:**

Between 0.3898 inches and 0.3948 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.5320 inches and 0.5940 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nutsteel comp 303 sleeve or steel comp 304 sleeve or steel comp 303se sleevesteel comp 4130 stem or steel comp 4140 stem or steel comp 8740 stem

**Material Specification:**

Mil-s-6758 military specification single material response nut or mil-s-5626 military specification single material response nut or mil-s-6049 military specification single material response nutqq-p-753 federal specification single material response sleeve or ams 5639 assn standard single material response sleeve or ams 5641 assn standard single material response sleeve mil-s-6758 military specification single material response stem or mil-s-5626 military specification single material response stem or mil-s-6049 military specification single material response stem

**Surface Treatment:**

Cadmium nut and chromate nutcadmium sleeve cadmium stem and chromate stem

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 2 federal specification single treatment response nutqq-p-416, type 1, cl 3 federal specification single treatment response sleeveqq-p-416, type 2, cl 2 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.